

SAT-3E Optical Laser Source

Key Features

- High sensitivity, multi output power
- Multi wavelengths optional, up to four wavelengths on two ports
- Automatic power-off, off time setting range 30~90mins
- Low battery alarm
- LCD display
- New-type conductive rubber switch, suitable for different operation environments.



Technical Specifications

SAT-3E series Models						
Model	3E03	3E04	3E05	3E06	3E07	3E08
Working Wavelength(nm)	1310/1550	650/1310/1550	850/1310/1550	650/1300	1310/1490/1550	1310/1550/1625
Output Power	850/1300/1310/1550/1490/1625: -6 (error: ± 0.2)					
Output Tone	850/1300/1310/1550 /1490/1625: CW, 270Hz, 1KHz, 2KHz; 650: CW					

Spectrum Width	≤ 5 nm
Output Stability	± 0.03 dB/15min; ± 0.05 dB/8h
Optical Identifying Distance	5km; 10km /15km optional (650nm)
Display	LCD
Power-off Time	30~99mins or none
Optical Interface	FC, SC, ST
Power Supply	AA alkaline batteries
Luminous Parts	LD
Operating Temperature	-10~+50°C
Storage Temperature	-40~+70°C
Dimension	L ×H ×W: 140×72×38 mm
Weight	0.3kg